

blofield AIR DESIGN

DoNuts Table



DoNuts - general specifications



Design: Dirk Wynants

Product dimensions:

Ø1: 1900mm Ø2: 1015mm H1: 762mm H2: 450mm


Installation:


Max air pressure: 3 PSI Inflation time: 3 minutes

Packaging specifications:

P1: 1590mm P2: 1800mm P3: 500mm

Gross weight: 32 kg
Net weight: 30,5 kg
Packing volume: 0,72 m3
Transport volume: 1,44 m3











Part:	Description:	Material and colour:	Outdoor:	Colour fastness:	Flammability:
Tube Cover	Fabric: for fabric specifications, see separate tube cover specification sheets.				
	Bottom protection:	Reinforced PVC, black	Waterproof	Good, UV sunlight: 7/8 ISO 105 B02	Flame retardant ISO 3795
Table	Weatherproof, durable table	High gloss polyester Signal White, RAL 9003	Waterproof	Good	Flame retardant NEN-EN13501-1 C
Table Mounting Point	Three mounting parts to connect the table to the tube easily	Stainless steel	Stainless	n.a.	Flame retardant NEN-EN13501-1 A1
Tube	Strong, high pressure tube. Will stay air tight for a long period. Tube can't be overinflated due to the air pressure relief valve.	Heavy duty rubber, black,	Waterproof	n.a.	Not flame retardant (but protected by cover)



DoNuts Solids - colours

Warning:

Do not us the DoNuts on water, it isn't a floating device. Do not sit or stand on the table.

Max pressure: 3 PSI







reddot design award







ECOAMIGO VIDAVERDE LDA

{{VAMIVY 澳美好生活有限公司 VidaVerde- ● Quality Product ● Quality Life ●